

Lumber Carts



Froedge makes four types of standard lumber carts to meet your production needs. All of them are built using the highest quality materials and components. Our carts are engineered to be long lasting, effective methods to stack and move your lumber for further processing or shipment.

Model 200-M



The Model 200-M is a two piece cart with some unique features. Each “end” has a three wheel “tri-cycle” arrangement that make them self-standing. One end has a back-plate and a bunk, the other end has only a bunk. While they have rigid uprights, they release the pack easier, because there is no front to back torque bind from connecting beams. The bunk uprights are made with 3” x 3” tubing, and the horizontal bunk rails are 3” x 5”. They work best when packs are made from uniform length lumber, but will accept random lengths as well if the bottom layer is made from lengths sufficient to build a base. They store exceptionally well, taking very little floor space when not being used.

MODEL 200-M SPECIFICATIONS

Wheel Size	10” Dia. x 3” W
Wheel Material	Phenolic
Weight Capacity	15,000 lbs.
Bunk Size	42” W x 40” T
Cart Dimensions	31” L x 55” W x 52” H

Model 100-C



The Model 100-C is a heavy-duty one-piece lumber cart with limited pivoting uprights. The main frame is fabricated from 4” angle iron, and the uprights from 4” channel. They are equipped with 8” x 3” casters. When the bunk is full, the uprights can be released and moved slightly off 90°, allowing the pack to be lifted out with no restrictions or hang ups.

MODEL 100-C SPECIFICATIONS

Wheel Size	8” Dia. x 3” W
Wheel Material	Casters
Weight Capacity	8,000 lbs.
Bunk Size	42” W x 48” T
Cart Dimensions	123” L x 45” W x 64” H

Lumber Carts



Model 100-H



The Model 100-H is a heavy-duty one-piece lumber cart with rigid uprights. These units are fabricated with 2" x 6" structural steel tubing main rails, and the uprights are made with 2" x 4" structural steel tubing. Each cart is equipped with 12" x 3" phenolic wheels. They can be ordered in eight or ten foot lengths, or can be custom-made to your requirements.

MODEL 100-H SPECIFICATIONS

Wheel Size	12" Dia. x 3" W
Wheel Material	Phenolic
Weight Capacity	8,000 lbs.
Bunk Size	42" W x 43" T
Cart Dimensions	96" or 120" L x 51" W x 60" H

Economy Carts



Froedge Economy carts are fabricated from 2" x 2" structural steel tubing main rails and uprights with gusseted joints. Each cart is equipped with 10" x 3" phenolic wheels with inserted bearings. These carts are perfect for users who process from 1,000 to 20,000 board feet per day, or those looking for the most affordable cart.

ECONOMY CART SPECIFICATIONS

Wheel Size	10" Dia. x 3" W
Wheel Material	Phenolic
Weight Capacity	6,500 lbs.
Bunk Size	42" W x 43" T
Cart Dimensions	124" L x 46" W x 60" H

Froedge Machine & Supply Company, Inc.

Tompkinsville, KY USA | 888-868-5891 | info@froedge.com

www.lumberhandling.com

Froedge - here to make it work